PAT-NO: JP02000302960A

DOCUMENT-IDENTIFIER: JP 2000302960 A

TITLE: OPTICAL FILM

PUBN-DATE: October 31, 2000

INVENTOR-INFORMATION:

NAME COUNTRY
AWAJI, HIROSHI N/A
NAKAMURA, MASAAKI N/A
SHIMOKAWA, MINORU N/A

ASSIGNEE-INFORMATION:

NAME COUNTRY KANEGAFUCHI CHEM IND CO LTD N/A

APPL-NO: JP11111502

APPL-DATE: April 19, 1999

INT-CL (IPC): C08L069/00, C08G064/18, C08L051/08, G02B005/30,

G02F001/13363

, G06F003/033 , C08J005/18

ABSTRACT:

PROBLEM TO BE SOLVED: To obtain an optical film exhibiting excellent transparency, low birefringence, heat resistance, moisture resistance and film formability by using a grafted polycarbonate resin composed of specific recurring unit.

SOLUTION: This optical film is obtained by using a grafted polycarbonate

resin composed of recurring unit of the formula (R1 to R4 are each H or methyl;

 ${\tt X}$ is a 5-10C cycloalkylene or 7-15C aralkylene having a grafted vinyl-based

polymer); wherein the grafted vinyl-based polymer mentioned above is pref. a

5/24/2007, EAST Version: 2.1.0.14

polymer made from a vinyl monomer such as an aromatic vinyl compound or

(meth)acrylic ester, or a (substituted) styrene. Furthermore, this optical

film contains pref. a plasticizer at 0.1-30 wt.% based on the grafted polycarbonate resin. This optical film has such characteristics is to be

≤70×10-13 cm2/dyne in photoelastic coefficient and 100-190°C in

glass transition temperature.

COPYRIGHT: (C) 2000, JPO